

TrueSTEAM™ Humidification System vs. Other Steam Humidification Competitive Comparison



PRODUCT				
FEATURES	Honeywell TrueSTEAM™	GENERALAire® DS15	EWC® AutoFlo S2000	The Honeywell Advantage
Remote-Mount Capability	Yes	Yes	No	Can be remotely mounted in tight or unconditioned spaces up to 20 feet from the system with remote-mount kit.
Footprint	11"W x 19"H x 8"L	14"W x 24"H x 8"L	8.25"W x 7.5"H x 12"L	TrueSTEAM's small footprint fits in more tight spaces.
Weight	12-15 lbs. with water	26 lbs. with water	15 lbs. with water	TrueSTEAM's weight makes it easier to install and service.
Duct Cut Size	1-3/4"	2-1/2"	6"W x 6"H	Requires only a 1-3/4" cut into ductwork.
Separate Mounting Bracket	Yes	No	No	Separate, lightweight mounting bracket for easy installation and accurate leveling.
Incoloy 600 Heating Element	Yes	No	No	Incoloy 600 is a material designed to inhibit mineral build-up.
Tools Required for Maintenance	No	Yes	Yes	No tools required to access and clean tank.
Terminals	Push	Screw	Screw	Push-in terminal blocks wire in half the time compared to screw terminals.
Dual-Action Water Valve	Yes	No	No	Solenoid design automatically fills and drains when needed to prevent debris build-up in the tank.
Packaged With In-Line Water Filter	Yes	No	No	Helps inhibit debris from entering tank.
Automatic End-of-Season Shutdown	Yes - after 48 hrs.	Yes - after 72 hrs.	No	Automatically empties tank after 48 hours of inactivity to avoid water stagnation.